



Material Safety Data Sheet

VOLVO BRAKE CLEANER (AEROSOL)

1. Product and company identification

| | |
|-----------------------------|--|
| Supplier | : Chemtool Incorporated 801 West Rockton Road Rockton, IL 61072 U.S.A. Tel: +01 815.957.4140 Fax: +01 815.624.0292 |
| Material uses | : Industrial applications: Cleaner; Aerosol. |
| Product code | : RMC9046731 |
| MSDS # | : 2103 |
| Validation date | : 9/26/2013. |
| In case of emergency | : INFOTRAC U.S. and Canada - 800.535.5053 Outside the U.S. and Canada - +01 352.323.3500 |

2. Hazards identification

Emergency overview

| | |
|---------------------------------------|---|
| Physical state | : Liquid [Aerosol.] |
| Color | : Colorless |
| Odor | : Lemon-like. |
| Signal word | : DANGER! |
| Hazard statements | : EXTREMELY FLAMMABLE AEROSOL. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. |
| Precautionary measures | : Do not breathe vapor or mist. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Wash thoroughly after handling. |
| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
| Routes of entry | : Dermal contact. Eye contact. Inhalation. Ingestion. |
| Potential acute health effects | |
| Inhalation | : No known significant effects or critical hazards. Vapors may cause drowsiness and dizziness. |
| Ingestion | : No known significant effects or critical hazards. |

2. Hazards identification

Skin : Slightly irritating to the skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Ingestion : No specific data.

Skin : Adverse symptoms may include the following:
irritation
redness

Eyes : Adverse symptoms may include the following:
pain or irritation
watering
redness

Medical conditions aggravated by over-exposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

| Name | CAS number | % |
|----------------|------------|-------|
| acetone | 67-64-1 | 50-70 |
| methyl acetate | 79-20-9 | 10-20 |
| Carbon dioxide | 124-38-9 | 10-20 |
| xylene | 1330-20-7 | 3-7 |
| heptane | 142-82-5 | 3-7 |

Canada

| Name | CAS number | % |
|----------------|------------|-------|
| acetone | 67-64-1 | 50-70 |
| methyl acetate | 79-20-9 | 10-20 |
| Carbon dioxide | 124-38-9 | 10-20 |
| xylene | 1330-20-7 | 3-7 |
| heptane | 142-82-5 | 3-7 |

3. Composition/information on ingredients

Mexico

Classification

| Name | CAS number | UN number | % | IDLH | H | F | R | Special |
|----------------|------------|-----------|-------|-----------|---|---|---|---------|
| acetone | 67-64-1 | UN1993 | 50-70 | 2500 ppm | 2 | 3 | 0 | - |
| methyl acetate | 79-20-9 | UN1993 | 10-20 | 3100 ppm | 2 | 3 | 0 | - |
| xylene | 1330-20-7 | UN1993 | 3-7 | 900 ppm | 2 | 3 | 0 | - |
| heptane | 142-82-5 | UN1993 | 3-7 | 750 ppm | 1 | 3 | 0 | - |
| Carbon dioxide | 124-38-9 | UN1956 | 10-20 | 40000 ppm | 0 | 0 | 0 | - |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

- Flammability of the product** : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5. Fire-fighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous.

- Storage** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

| Ingredient | Exposure limits |
|----------------|---|
| acetone | <p>ACGIH TLV (United States, 3/2012). TWA: 500 ppm 8 hours. TWA: 1188 mg/m³ 8 hours. STEL: 750 ppm 15 minutes. STEL: 1782 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 750 ppm 8 hours. TWA: 1800 mg/m³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 2400 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 1/2013). TWA: 250 ppm 10 hours. TWA: 590 mg/m³ 10 hours.</p> <p>OSHA PEL (United States, 6/2010). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m³ 8 hours.</p> |
| methyl acetate | <p>ACGIH TLV (United States, 3/2012). TWA: 200 ppm 8 hours. TWA: 606 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 757 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 200 ppm 8 hours. TWA: 610 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 760 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 1/2013). TWA: 200 ppm 10 hours. TWA: 610 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 760 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 6/2010). TWA: 200 ppm 8 hours. TWA: 610 mg/m³ 8 hours.</p> |
| Carbon dioxide | <p>ACGIH TLV (United States, 1/2011). TWA: 5000 ppm 8 hours. TWA: 9000 mg/m³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 10000 ppm 8 hours. TWA: 18000 mg/m³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 6/2009). TWA: 5000 ppm 10 hours. TWA: 9000 mg/m³ 10 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 6/2010).</p> |

8. Exposure controls/personal protection

| | |
|---------|--|
| xylene | <p>TWA: 5000 ppm 8 hours. TWA: 9000 mg/m³ 8 hours.</p> <p>ACGIH TLV (United States, 3/2012). TWA: 100 ppm 8 hours. TWA: 434 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.</p> |
| heptane | <p>ACGIH TLV (United States, 3/2012). TWA: 400 ppm 8 hours. TWA: 1640 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2050 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 1600 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2000 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 1/2013). TWA: 85 ppm 10 hours. TWA: 350 mg/m³ 10 hours. CEIL: 440 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 6/2010). TWA: 500 ppm 8 hours. TWA: 2000 mg/m³ 8 hours.</p> |

Canada

| <u>Occupational exposure limits</u> | | TWA (8 hours) | | | STEL (15 mins) | | | Ceiling | | | Notations |
|-------------------------------------|-----------------|---------------|-------------------|-------|----------------|-------------------|-------|---------|-------------------|-------|-----------|
| Ingredient | List name | ppm | mg/m ³ | Other | ppm | mg/m ³ | Other | ppm | mg/m ³ | Other | |
| acetone | US ACGIH 3/2012 | 500 | 1188 | - | 750 | 1782 | - | - | - | - | |
| | AB 4/2009 | 500 | 1200 | - | 750 | 1800 | - | - | - | - | |
| | BC 4/2012 | 250 | - | - | 500 | - | - | - | - | - | |
| | ON 1/2013 | 500 | 1188 | - | 750 | 1782 | - | - | - | - | |
| | QC 12/2012 | 500 | 1190 | - | 1000 | 2380 | - | - | - | - | |
| methyl acetate | US ACGIH 3/2012 | 200 | 606 | - | 250 | 757 | - | - | - | - | |
| | AB 4/2009 | 200 | 606 | - | 250 | 757 | - | - | - | - | |
| | BC 4/2012 | 200 | - | - | 250 | - | - | - | - | - | |
| | ON 1/2013 | 200 | 606 | - | 250 | 757 | - | - | - | - | |
| | QC 12/2012 | 200 | 606 | - | 250 | 757 | - | - | - | - | |
| Carbon dioxide | US ACGIH 1/2011 | 5000 | 9000 | - | 30000 | 54000 | - | - | - | - | |
| | AB 4/2009 | 5000 | 9000 | - | 30000 | 54000 | - | - | - | - | |
| | BC 9/2011 | 5000 | - | - | 15000 | - | - | - | - | - | |
| | ON 7/2010 | 5000 | 9000 | - | 30000 | 54000 | - | - | - | - | |
| | QC 9/2011 | 5000 | 9000 | - | 30000 | 54000 | - | - | - | - | |
| xylene | US ACGIH 3/2012 | 100 | 434 | - | 150 | 651 | - | - | - | - | |
| | AB 4/2009 | 100 | 434 | - | 150 | 651 | - | - | - | - | |

8. Exposure controls/personal protection

| | | | | | | | | | | | |
|------------|-----------------|------|------|-----|------|------|---|---|---|---|---|
| heptane | BC 4/2012 | 100 | - | - | 150 | - | - | - | - | - | - |
| | ON 1/2013 | 100 | 434 | - | 150 | 651 | - | - | - | - | - |
| | QC 12/2012 | 100 | 434 | - | 150 | 651 | - | - | - | - | - |
| | US ACGIH 3/2012 | 400 | 1640 | - | 500 | 2050 | - | - | - | - | - |
| | AB 4/2009 | 400 | 1640 | - | 500 | 2050 | - | - | - | - | - |
| | BC 4/2012 | 400 | - | - | 500 | - | - | - | - | - | - |
| | ON 1/2013 | 400 | 1640 | - | 500 | 2050 | - | - | - | - | - |
| QC 12/2012 | 400 | 1640 | - | 500 | 2050 | - | - | - | - | - | |

Mexico

Occupational exposure limits

| Ingredient | Exposure limits |
|-------------------|--|
| acetone | NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 1000 ppm 8 hours. LMPE-PPT: 2400 mg/m ³ 8 hours. LMPE-CT: 3000 mg/m ³ 15 minutes. LMPE-CT: 1260 ppm 15 minutes. |
| methyl acetate | NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 200 ppm 8 hours. LMPE-PPT: 610 mg/m ³ 8 hours. LMPE-CT: 760 mg/m ³ 15 minutes. LMPE-CT: 250 ppm 15 minutes. |
| Carbon dioxide | NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 5000 ppm 8 hours. LMPE-PPT: 9000 mg/m ³ 8 hours. LMPE-CT: 27000 mg/m ³ 15 minutes. LMPE-CT: 15000 ppm 15 minutes. |
| xylene | NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 100 ppm 8 hours. LMPE-PPT: 435 mg/m ³ 8 hours. LMPE-CT: 655 mg/m ³ 15 minutes. LMPE-CT: 150 ppm 15 minutes. |
| heptane | NOM-010-STPS (Mexico, 9/2000). Absorbed through skin. LMPE-PPT: 400 ppm 8 hours. LMPE-PPT: 1600 mg/m ³ 8 hours. LMPE-CT: 2000 mg/m ³ 15 minutes. LMPE-CT: 500 ppm 15 minutes. |

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

- Physical state** : Liquid [Aerosol.]
- Flash point** : Closed cup: -20°C (-4°F)
- Auto-ignition temperature** : 455 to 527°C (851 to 980.6°F)
- Flammable limits** : Lower: 1%
Upper: 16%
- Color** : Colorless
- Odor** : Lemon-like.
- pH** : Not applicable.
- Boiling/condensation point** : 57 to 143°C (134.6 to 289.4°F)
- Melting/freezing point** : Not available.
- Density** : 0.84 to 0.88 g/cm³
- Vapor pressure** : Not available.
- Vapor density** : >1 [Air = 1]
- Volatility** : 10% (w/w)
- Evaporation rate** : >1 (butyl acetate = 1)

9. Physical and chemical properties

| | |
|----------------------------------|---|
| Viscosity | : Not available. |
| Dispersibility properties | : Not available. |
| Solubility | : Insoluble in the following materials: cold water. |
| Aerosol product | |
| Type of aerosol | : Spray |
| Heat of combustion | : 24.85 kJ/g |

10. Stability and reactivity

| | |
|---|--|
| Chemical stability | : The product is stable. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |

11. Toxicological information

United States

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|----------------------|----------|
| acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| methyl acetate | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | >5 g/kg | - |
| xylene | LC50 Inhalation Gas. | Rat | 5000 ppm | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| heptane | LC50 Inhalation Gas. | Rat | 48000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Rat | 103 g/m ³ | 4 hours |

Conclusion/Summary : No known significant effects or critical hazards.

Chronic toxicity

Conclusion/Summary : Contains material that may cause target organ damage, based on animal data.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| acetone | Eyes - Mild irritant | Human | - | 186300 parts per million | - |
| | Eyes - Mild irritant | Rabbit | - | 10 microliters | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 395 milligrams | - |
| methyl acetate | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |

11. Toxicological information

| | | | | | |
|--------|--------------------------|--------|---|-------------------------|---|
| xylene | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 87 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 milligrams | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 microliters | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 100 Percent | - |

Conclusion/Summary

- Skin** : Moderately irritating to the skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Eyes** : Causes eye irritation. Risk of serious damage to eyes.
- Respiratory** : Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. Vapors may cause drowsiness and dizziness.

Sensitizer

Conclusion/Summary

- Skin** : No specific information is available in our database regarding the skin sensitizing properties of this product. Sensitization not suspected for humans.
- Respiratory** : Sensitization not suspected for humans.

Carcinogenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Carcinogenicity not suspected for humans.

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|------|
| acetone | A4 | - | - | - | - | - |
| xylene | A4 | 3 | - | - | - | - |

Mutagenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Mutagenicity not suspected for humans.

Teratogenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Teratogenicity not suspected for humans.

Reproductive toxicity

Conclusion/Summary

- : There are no data available on the mixture itself. Not considered to be dangerous to humans, according to our database.

Canada

Acute toxicity

11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|----------------------|----------|
| acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| methyl acetate | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | >5 g/kg | - |
| xylene | LC50 Inhalation Gas. | Rat | 5000 ppm | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| heptane | LC50 Inhalation Gas. | Rat | 48000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Rat | 103 g/m ³ | 4 hours |

Conclusion/Summary : No known significant effects or critical hazards.

Chronic toxicity

Conclusion/Summary : Contains material that may cause target organ damage, based on animal data.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| acetone | Eyes - Mild irritant | Human | - | 186300 parts per million | - |
| | Eyes - Mild irritant | Rabbit | - | 10 microliters | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| methyl acetate | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 395 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| xylene | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 87 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 milligrams | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 microliters | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 100 Percent | - |

Conclusion/Summary

Skin : Moderately irritating to the skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes : Causes eye irritation. Risk of serious damage to eyes.

Respiratory : Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. Vapors may cause drowsiness and dizziness.

Sensitizer

Conclusion/Summary

Skin : No specific information is available in our database regarding the skin sensitizing properties of this product. Sensitization not suspected for humans.

Respiratory : Sensitization not suspected for humans.

11. Toxicological information

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself. Carcinogenicity not suspected for humans.

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|------|
| acetone | A4 | - | - | - | - | - |
| xylene | A4 | 3 | - | - | - | - |

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself. Mutagenicity not suspected for humans.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself. Teratogenicity not suspected for humans.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself. Not considered to be dangerous to humans, according to our database.

Mexico

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|----------------------|----------|
| acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| methyl acetate | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | >5 g/kg | - |
| xylene | LC50 Inhalation Gas. | Rat | 5000 ppm | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| heptane | LC50 Inhalation Gas. | Rat | 48000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Rat | 103 g/m ³ | 4 hours |

Conclusion/Summary : No known significant effects or critical hazards.

Chronic toxicity

Conclusion/Summary : Contains material that may cause target organ damage, based on animal data.

Irritation/Corrosion

| Product/ingredient name | Result | Score | Score | Exposure | Observation |
|-------------------------|--------------------------|--------|-------|--------------------------|-------------|
| acetone | Eyes - Mild irritant | Human | - | 186300 parts per million | - |
| | Eyes - Mild irritant | Rabbit | - | 10 microliters | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| methyl acetate | Skin - Mild irritant | Rabbit | - | 395 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | | | | | |

11. Toxicological information

| | | | | | |
|--------|--------------------------|--------|---|-------------------------|---|
| xylene | Eyes - Mild irritant | Rabbit | - | 87 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 milligrams | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 microliters | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 100 Percent | - |

Conclusion/Summary

- Skin** : Moderately irritating to the skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Eyes** : Causes eye irritation. Risk of serious damage to eyes.
- Respiratory** : Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. Vapors may cause drowsiness and dizziness.

Sensitizer

Conclusion/Summary

- Skin** : No specific information is available in our database regarding the skin sensitizing properties of this product. Sensitization not suspected for humans.
- Respiratory** : Sensitization not suspected for humans.

Carcinogenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Carcinogenicity not suspected for humans.

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|------|
| acetone | A4 | - | - | - | - | - |
| xylene | A4 | 3 | - | - | - | - |

Mutagenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Mutagenicity not suspected for humans.

Teratogenicity

Conclusion/Summary

- : There are no data available on the mixture itself. Teratogenicity not suspected for humans.

Reproductive toxicity

Conclusion/Summary

- : There are no data available on the mixture itself. Not considered to be dangerous to humans, according to our database.

12. Ecological information

- Ecotoxicity** : No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

12. Ecological information

| Product/ingredient name | Result | Species | Exposure |
|--------------------------|-------------------------------------|--|----------|
| acetone | Acute EC50 20.565 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 100 mg/l Fresh water | Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - Daphniidae | 21 days |
| methyl acetate xylene | Acute LC50 320000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| | Acute LC50 8500 µg/l Marine water | Fish - Pimephales promelas | 96 hours |
| heptane | Acute LC50 13400 µg/l Fresh water | Crustaceans - Palaemonetes pugio | 48 hours |
| | Acute LC50 375000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | | Fish - Oreochromis mossambicus | 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

Persistence/degradability

Conclusion/Summary : This product has not been tested for biodegradation. Expected to be biodegradable. This product is not expected to bioaccumulate through food chains in the environment.

Canada

Aquatic ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|--------------------------|-------------------------------------|--|----------|
| acetone | Acute EC50 20.565 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 100 mg/l Fresh water | Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - Daphniidae | 21 days |
| methyl acetate xylene | Chronic NOEC 0.1 ml/L Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| | Acute LC50 320000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| heptane | Acute LC50 8500 µg/l Marine water | Crustaceans - Palaemonetes pugio | 48 hours |
| | Acute LC50 13400 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 375000 µg/l Fresh water | Fish - Oreochromis mossambicus | 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

Persistence/degradability

Conclusion/Summary : This product has not been tested for biodegradation. Expected to be biodegradable. This product is not expected to bioaccumulate through food chains in the environment.

Mexico

Aquatic ecotoxicity

12. Ecological information

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-------------------------------------|--|----------|
| acetone | Acute EC50 20.565 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 100 mg/l Fresh water | Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - Daphniidae | 21 days |
| methyl acetate | Chronic NOEC 0.1 ml/L Fresh water | Daphnia - Daphnia magna - Neonate | 21 days |
| | Acute LC50 320000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| xylene | Acute LC50 8500 µg/l Marine water | Crustaceans - Palaemonetes pugio | 48 hours |
| | Acute LC50 13400 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| heptane | Acute LC50 375000 µg/l Fresh water | Fish - Oreochromis mossambicus | 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

Persistence/degradability

Conclusion/Summary : This product has not been tested for biodegradation. Expected to be biodegradable. This product is not expected to bioaccumulate through food chains in the environment.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.





Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.



14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|-----------|----------------------|---------|-----|-------|------------------------|
| | | | | | | |

14. Transport information

| | | | | | | |
|------------------------------|--------|-------------------------------|-----|---|---|---|
| DOT Classification | UN1950 | Aerosols RQ (xylene, acetone) | 2.1 | - |  | <p>Reportable quantity 2155.2 lbs / 978.45 kg [300.56 gal / 1137.7 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.</p> <p>Packaging instruction Passenger aircraft Quantity limitation: 75 kg</p> <p>Cargo aircraft Quantity limitation: 150 kg</p> <p>Special provisions 153, N82</p> |
| TDG Classification | UN1950 | AEROSOLS | 2.1 | - |  | <p>Explosive Limit and Limited Quantity Index 1</p> <p>Passenger Carrying Road or Rail Index 75</p> |
| Mexico Classification | UN1950 | AEROSOLS | 2.1 | - |  | <p>Special provisions 63, 190, 277</p> |
| ADR/RID Class | UN1950 | AEROSOLS | 2 | - |  | <p>Limited quantity 1 L</p> <p>Special provisions 190 327 625 344</p> <p>Tunnel code (D)</p> |
| | | | | | | |

14. Transport information

| | | | | | | |
|-----------------------|--------|---------------------|-----|---|---|---|
| IMDG Class | UN1950 | AEROSOLS | 2.1 | - |  | Emergency schedules (EmS) F-D, S-U Special provisions 63, 190, 277, 327, 959, 344 |
| IATA-DGR Class | UN1950 | Aerosols, flammable | 2.1 | - |  | Passenger and Cargo Aircraft Quantity limitation: 75 kg Packaging instructions: 203 Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 203 Limited Quantities - Passenger Aircraft Quantity limitation: 30 kg Packaging instructions: Y203 Special provisions A145, A167 |

PG* : Packing group

15. Regulatory information

United States

- HCS Classification** : Flammable aerosol
Irritating material
Target organ effects
- U.S. Federal regulations** : **TSCA 8(a) PAIR**: methyl acetate; heptane
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
TSCA 12(b) one-time export: heptane
United States inventory (TSCA 8b): All components are listed or exempted.
SARA 302/304: No products were found.
SARA 311/312 Hazards identification: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 311: xylene
- Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed
- Clean Air Act Section 602 Class I Substances** : Not listed

15. Regulatory information

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Listed

SARA 313

| | Product name | CAS number | Concentration |
|--|--------------|------------|---------------|
| Form R - Reporting requirements | : xylene | 1330-20-7 | 3-7 |
| Supplier notification | : xylene | 1330-20-7 | 3-7 |

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

- Connecticut Carcinogen Reporting** : None of the components are listed.
- Connecticut Hazardous Material Survey** : None of the components are listed.
- Florida substances** : None of the components are listed.
- Illinois Chemical Safety Act** : None of the components are listed.
- Illinois Toxic Substances Disclosure to Employee Act** : None of the components are listed.
- Louisiana Reporting** : None of the components are listed.
- Louisiana Spill** : None of the components are listed.
- Massachusetts Spill** : None of the components are listed.
- Massachusetts Substances** : The following components are listed: ACETONE; METHYL ACETATE; CARBON DIOXIDE; XYLENE; HEPTANE (N-HEPTANE)
- Michigan Critical Material** : None of the components are listed.
- Minnesota Hazardous Substances** : None of the components are listed.
- New Jersey Spill** : None of the components are listed.
- New Jersey Toxic Catastrophe Prevention Act** : None of the components are listed.
- New Jersey Hazardous Substances** : The following components are listed: ACETONE; 2-PROPANONE; METHYL ACETATE; ACETIC ACID, METHYL ESTER; CARBON DIOXIDE; CARBONIC ACID GAS; XYLENES; BENZENE, DIMETHYL-; n-HEPTANE; HEPTANE
- New York Acutely Hazardous Substances** : The following components are listed: Acetone; 2-Propanone; Xylene (mixed)
- New York Toxic Chemical Release Reporting** : None of the components are listed.
- Pennsylvania RTK Hazardous Substances** : The following components are listed: 2-PROPANONE; ACETIC ACID, METHYL ESTER; CARBON DIOXIDE; BENZENE, DIMETHYL-; HEPTANE
- Rhode Island Hazardous Substances** : None of the components are listed.

California Prop. 65

None of the components are listed.

15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada

WHMIS (Canada) : Class B-2: Flammable liquid
Class B-5: Flammable aerosol.
Class D-2A: Material causing other toxic effects (Very toxic).
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Volatile organic compounds; Xylene (all isomers); Heptane (all isomers)


CEPA Toxic substances : The following components are listed: Volatile organic compounds; Carbon dioxide

Canada inventory; DSL/ NDSL : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification :



International regulations

International lists :

- Australia inventory (AICS)**: All components are listed or exempted.
- China inventory (IECSC)**: All components are listed or exempted.
- Japan inventory**: All components are listed or exempted.
- Korea inventory**: All components are listed or exempted.
- Malaysia Inventory (EHS Register)**: Not determined.
- New Zealand Inventory of Chemicals (NZIoC)**: All components are listed or exempted.
- Philippines inventory (PICCS)**: All components are listed or exempted.
- Taiwan inventory (CSNN)**: Not determined.
- Europe inventory** : All components are listed or exempted.

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

16. Other information

Label requirements : EXTREMELY FLAMMABLE AEROSOL. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Hazardous Material Information System (U.S.A.) :

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 4 |
| Physical hazards | | 0 |
| | | B |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 9/26/2013.

Date of previous issue : 9/26/2013.

Version : 1.02

Prepared by : Regulatory Department, Chemtool Inc.

▣ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.