According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:	SDS Number:	Print Date: 08/17/2020
1.0	05/20/2020	800010039295	Date of last issue: -

SECTION 1. IDENTIFICATION

Product name : VOLVO I-Shift Transmission Fluid 75W-80

Product code : 001I5124

Manufacturer or supplier's details

Manufacturer/Supplier	: Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request	:
Customer Service	: (+1) 877-276-7285

Emergency telephone number

Spill Information	:	877-504-9351
Health Information	:	877-242-7400

Recommended use of the chemical and restrictions on use

Recommended use : Transmission oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms :	No Hazard Symbol required
Signal word	No signal word
Hazard statements	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements :	Prevention: No precautionary phrases. Response: No precautionary phrases.
	Storage: No precautionary phrases.
	Disposal:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:	SDS
1.0	05/20/2020	800

S Number: 0010039295 Print Date: 08/17/2020 Date of last issue: -

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

•

Mixture

Chemical nature	 Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu-
	ent.

Hazardous components

Substance / Mixture

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Alkaryl amine	bis(nonylphenyl)amine	36878-20-3	1-3
Heterocyclic ether	Thiophene, tetrahydro-, 1,1-dioxide, 3- (C9-11- isoalkyloxy) derivs., C10- rich	398141-87-2	1 - 1.4
Amine phosphate	Amines, C12- 14-alkyl, reac- tion products with hexanol, phosphorus oxide (P2O5), phosphorus sulfide (P2S5) and propylene oxide	91745-46-9	0.75 - 1.05

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Versi 1.0	ion	Revision Date: 05/20/2020		9S Number: 0010039295	Print Date: 08/17/2020 Date of last issue: -
				•	on occurs, obtain medical attention.
	In case	of eye contact	:	Remove contact le rinsing.	bious quantities of water. enses, if present and easy to do. Continue on occurs, obtain medical attention.
	lf swalld	owed	:		tment is necessary unless large quantities wever, get medical advice.
;		portant symptoms ects, both acute and I	:	of black pustules a	signs and symptoms may include formation and spots on the skin of exposed areas. ult in nausea, vomiting and/or diarrhoea.
	Protecti	on of first-aiders	:		ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.
I	medica	on of any immediate I attention and special Int needed	:	Treat symptomation	cally.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	:	Avoid contact with skin and eyes.
tive equipment and emer-		
gency procedures		

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

ersion .0	Revision Date: 05/20/2020		0S Number: 0010039295	Print Date: 08/17/2020 Date of last issue: -
Enviro	onmental precautions	:	nation. Prevent fr	containment to avoid environmental contam om spreading or entering drains, ditches or and, earth, or other appropriate barriers.
			Local authorities cannot be contain	should be advised if significant spillages ned.
	ods and materials for inment and cleaning up	:	Prevent from spre or other containm Reclaim liquid dir Soak up residue	ilt. Avoid accidents, clean up immediately. eading by making a barrier with sand, earth ent material. ectly or in an absorbent. with an absorbent such as clay, sand or othe and dispose of properly.
Additi	onal advice	:	see Section 8 of t	selection of personal protective equipment his Safety Data Sheet. disposal of spilled material see Section 13 c Sheet.

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:
1.0	05/20/2020

SDS Number: 800010039295 Print Date: 08/17/2020 Date of last issue: -

peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
		Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
		General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:	SDS Number:	Print Date: 08/17/2020
1.0	05/20/2020	800010039295	Date of last issue: -

equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks	:	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Vers 1.0	sion	Revision Date: 05/20/2020		9S Number: 0010039295	Print Date: 08/17/2020 Date of last issue: -	
	Eye pro	otection	:		lled such that it could be splashed into eyes, ar is recommended.	
	Skin ar	nd body protection	:	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves. 		
	Protect	ive measures	:	Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers.		
	Therma	al hazards	:	Not applicable		
	Enviro	nmental exposure co	ntro	ols		
	Genera	al advice	:	vant environment of the environment necessary, preve charged to waste municipal or indus discharge to surfa Local guidelines of	measures to fulfill the requirements of rele- al protection legislation. Avoid contamination at by following advice given in Section 6. If ant undissolved material from being dis- water. Waste water should be treated in a strial waste water treatment plant before ace water. on emission limits for volatile substances d for the discharge of exhaust air containing	
SEC	CTION 9	. PHYSICAL AND CH	EMI		S	
	Appear	rance	:	Liquid at room te	emperature.	
	Colour		:	amber		
	Odour		:	Slight hydrocarb	on	
	Odour	Threshold	:	Data not availab	le	
	рН		:	Not applicable		
	pour po	bint	:	<= -48 °C / <= -5 Method: ISO 301		
	Initial b range	oiling point and boiling	:	> 280 °C / 536 °I estimated value(
	Flash p	point	:	245 °C / 473 °F		

Method: ISO 2592

Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

ersion 0	Revision Date: 05/20/2020		S Number: 010039295	Print Date: 08/17/2020 Date of last issue: -
	r explosion limit / Lower nability limit	:	Typical 1 %(V)	
Vapo	ur pressure	:	< 0.5 Pa (20 °C /	68 °F)
			estimated value(5)
Relat	ive vapour density	:	> 1 estimated value(s)
Dens	ity	:	849 kg/m3 (15.0 Method: ISO 121	
	ility(ies) ater solubility	:	negligible	
Sc	blubility in other solvents	:	Data not availabl	e
	ion coefficient: n- ol/water	:		ation on similar products)
Auto-	ignition temperature	:	> 320 °C / 608 °I	-
Deco	mposition temperature	:	Data not availab	e
Visco Vi	sity scosity, dynamic	:	Data not availabl	е
Vi	scosity, kinematic	:	56 mm2/s (40.0	°C / 104.0 °F)
			Method: ISO 310	4
			9.3 - 10.0 mm2/s	(100 °C / 212 °F)
			Method: ISO 310	4
Explo	sive properties	:	Not classified	
Oxidi	zing properties	:	Data not availabl	e
Cond	uctivity	:	This material is r	ot expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version 1.0	Revision Date: 05/20/2020	SDS Number: 800010039295	Print Date: 08/17/2020 Date of last issue: -
Incom	itions to avoid npatible materials rdous decomposition icts	: Strong oxidisin	mperature and direct sunlight. Ig agents. tion if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
		the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Amine phosphate:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:
1.0	05/20/2020

SDS Number: 800010039295 Print Date: 08/17/2020 Date of last issue: -

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

Components:

Amine phosphate:

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:
1.0	05/20/2020

SDS Number: 800010039295 Print Date: 08/17/2020 Date of last issue: -

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
Product: Toxicity to fish (Acute toxici- ty)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae (Acute tox- icity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	Remarks: Data not available

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Vers 1.0	sion	Revision Date: 05/20/2020		DS Number: 0010039295	Print Date: 08/17/2020 Date of last issue: -
		y to microorganisms toxicity)	:	Remarks: Data n	ot available
	Persis	stence and degradabi	lity		
	<u>Produ</u> Biodeç	<u>ct:</u> gradability	:	Major constituent	adily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
	Bioac	cumulative potential			
	<u>Produ</u> Bioaco	<u>ct:</u> cumulation	:	Remarks: Contai cumulate.	ns components with the potential to bioac-
	Mobili	ty in soil			
	<u>Produ</u> Mobilit			Domorkov Liquid	under meet en ironmentel conditione
	Mobilit	y			under most environmental conditions. will adsorb to soil particles and will not be
				Remarks: Floats	on water.
	Other	adverse effects			
	<u>Produ</u>				
	Additic mation	onal ecological infor-	:	ozone creation per Product is a mixter	zone depletion potential, photochemical otential or global warming potential. ure of non-volatile components, which will not r in any significant quantities under normal
				Poorly soluble m Causes physical	xture. fouling of aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version 1.0	Revision Date: 05/20/2020	SDS Number: 800010039295	Print Date: 08/17/2020 Date of last issue: -
Conta	minated packaging	Dispose in ac to a recogniz the collector Disposal sho	or used product is dangerous waste. ccordance with prevailing regulations, preferably ed collector or contractor. The competence of or contractor should be established beforehand. uld be in accordance with applicable regional, local laws and regulations.
Local Rema	legislation ırks	•	uld be in accordance with applicable regional, local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., The components with RQs are given for information., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:	SDS Number:	Print Date: 08/17/2020
1.0	05/20/2020	800010039295	Date of last issue: -

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated light

64742-47-8

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
		its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
Abbreviations and Acronyms	:	The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes	
CAS = Chemical Abstrats Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DSL = Canada Domestic Substance List EC = European Commission ECS0 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and To: gy Of Chemicals ECHA = European Center on Ecotoxicology and To: gy Of Chemicals ECHA = European Chemicals Agency EINECS = The European Inventory of Existing Comme Chemical Substances ELS0 = Effective Concentration fifty ENCS = Japanese Existing and New Chemical Substar Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification a Labelling of Chemicals Inventory ILS0 = Inhibitory Concentration fifty ILS0 = Inhibitory Curventian Maritime Dangerous Goods INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for determination of polycyclic aromatics DMS0-extractabl KEC1 = Korea Existing Chemicals Inventory LDS0 = Lethal Dose fifty per cent. LLE/L/L = Lethal Loading/Effective Loading/Inhibitory ILS0 DS0 = Lethal Dose Fifty per cent. LLE/L/L = Lethal Loading/Effective Loading/Inhibitory IN DS0 = Lethal Dose fifty per cent. LLE/L/L = Lethal Loading/Effective Loading/Inhibitory IN DS0 = Lethal Dose fifty per cent. LLE/L/L = Lethal Loading/Effective Loading/Inhibitory IN DS0 = Lethal Loading/Effective Loading/Inhibitory IN DS0 = Lethal Dose fifty per cent. LLE/L/L = Voccupational Exposure - High Production V DS1 = Persistent, Bioaccumulative and Toxic PICCS = Predicted No Effect Concentration fitty LLS0 = Lethal Loading/Effective Loading/Inhibitory IN CLS1 = Shin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average VPS = very Persistent and very Bioaccumulative	rcial aces ading of Ob- olume al

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

VOLVO I-Shift Transmission Fluid 75W-80

Version	Revision Date:	SDS Number:	Print Date: 08/17/2020
1.0	05/20/2020	800010039295	Date of last issue: -

A vertical bar () in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	05/20/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN