

V O L V O



Proven Genuine Performance, Proved Genuine Protection

VOLVO VCS2 EXTENDED LIFE COOLANT

- Advanced POAT technology guarantees cooling system protection for 1.5 million miles, 10 years, or 36,000 hours
- Perfect 10 water pump test rating*
- Outstanding protection against corrosion, cavitation, scale, and deposits
- Nitrite Free and 2EHA Free Formula
- Eliminates the need for Extenders and Supplemental Coolant Additives (SCA)



VOLVO VCS2 EXTENDED LIFE COOLANT

Proven Genuine Performance, Proved Genuine Protection

Volvo VCS2 Antifreeze/Coolant is an advanced phosphated enhanced organic acid technology (POAT) engineered to deliver the highest level of performance for today's heavy duty engines. Corrosion inhibitors within this product provide fast-acting, long-lasting protection to all cooling system metals including controlled atmosphere brazed (CAB) and cast aluminum components. Proprietary scale-fighting inhibitors help prevent deposit formation to maximize heat transfer. Volvo VCS2 Antifreeze/Coolant is free of nitrite and 2-ethylhexanoic acid (2EHA) and is compatible with all system gaskets and hose materials.

Volvo VCS2 meets or exceeds these specifications and manufacturers' requirements:

- AGCO
- ASTM D3306
- ASTM D6210
- ASTM D7583
- CAT EC-1
- CNH EG-3, EG-4
- Cummins CES 14439
- Cummins CES 14603
- Cummins CES 14636
- Detroit DFS 93K217
- Deutz DQC CB-14
- Fendt
- Ford WSS-M97B57-A1
- International
- Isuzu
- JIS K2234
- John Deere H24
- Komatsu
- Kubota
- Mack
- MAN 324 Type SNF
- Mercedes DBL 7700
- MTU MTL 5048
- Navistar MPAPSB-1 Type IIIA
- PACCAR
- Peterbilt
- SAE J1034
- TMC RP338
- TMC RP351
- TMC RP364
- Waukesha

Recommended for use where the following equipment or specifications are cited:

- Cummins
- Caterpillar
- Freightliner
- International
- Isuzu
- Komatsu
- PACCAR
- Peterbilt
- Volvo

Advantages and Benefits

- Guaranteed Life-of-the-Engine 1,500,000 mile coolant*, 10 years, or 36,000 hours
- Advanced POAT Technology
- Works in all medium and heavy duty diesel, gasoline, and natural gas engine applications
- Nitrite-free to provide excellent protection for CAB and cast aluminum alloys
- 2-EHA free formula ensures exceptional long term elastomer compatibility
- Eliminates the need for Extenders, SCAs, and chemically charged filters

* Requires proper maintenance including a complete cooling system flush and fill and subsequent top-off as needed.

Delivers outstanding water pump protection

Pump Rating at 300 hrs: "Perfect 10" Performance in an Extended 300 Hr ASTM Severe Duty Test



Highest test rating

Like-new condition

No corrosion, erosion, discoloration

Product Number	Country	Product Description	Package
MVBVCS25050JUG	USA/Canada	Volvo VCS2 50/50 Pre-Mix Coolant 6/1 Gallon Case	Gallon Jug
MVBVCS25050DRUM	USA/Canada	Volvo VCS2 50/50 Pre-Mix Coolant 55 Gallon Drum	Drum
MVBVCS25050TOTE	USA/Canada	Volvo VCS2 50/50 Pre-Mix Coolant 275 Gallon Tote	Tote
MVBVCS25050BULK	USA/Canada	Volvo VCS2 50/50 Pre-Mix Coolant Bulk	Bulk
MVBVCS2CONJUG	USA/Canada	Volvo VCS2 Concentrate Coolant 6/1 Gallon Case	Gallon Jug
MVBVCS2CONDRUM	USA/Canada	Volvo VCS2 Concentrate Coolant 55 Gallon Drum	Drum

VolvoTrucks.us | VolvoTrucks.ca

©2025 Volvo Trucks, Inc. All rights reserved. Volvo and all other marks contained herein are registered trademarks of Volvo Trucks, Inc. and/or Volvo Trucks, Inc. affiliated companies. All other marks contained herein are the property of their respective owners.

V O L V O

PV960-V-061225